COPY 1

REPORT No. FAA-RD-76-35

# INDEX TO ILS/VOR-RELATED TOPICS CONTAINED IN TECHNICAL REPORTS PRODUCED BY THE OHIO UNIVERSITY AVIONICS ENGINEERING CENTER DURING THE PERIOD 1965-1975

HARRY L. GRAHAM

AVIONICS ENGINEERING CENTER
DEPARTMENT OF ELECTRICAL ENGINEERING
OHIO UNIVERSITY
ATHENS, OHIO 45701

NAFEC
LIBRARY
MAR 23 '76

DECEMBER 1975

Document is available to the public through the
National Technical Information Service,
Springfield, Virginia 22161.

Prepared for

**U.S. DEPARTMENT OF TRANSPORTATION**
**FEDERAL AVIATION ADMINISTRATION**
**Systems Research & Development Service**
**Washington, D.C. 20590**

NOTICE

This document is disseminated under the sponsorship of the Department of Transportation in the interest of information exchange. The United States Government assumes no liability for its contents or use thereof.

**Technical Report Documentation Page**

| | | |
|---|---|---|
| 1. Report No. FAA-RD-76-35 | 2. Government Accession No. | 3. Recipient's Catalog No. |
| 4. Title and Subtitle INDEX TO ILS/VOR-RELATED TOPICS CONTAINED IN TECHNICAL REPORTS PRODUCED BY THE OHIO UNIVERSITY AVIONICS ENGINEERING CENTER DURING THE PERIOD 1965-1975 | | 5. Report Date December 1975 |
| | | 6. Performing Organization Code |
| 7. Author(s) Harry L. Graham | | 8. Performing Organization Report No. EER 5-23 |
| 9. Performing Organization Name and Address Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio 45701 | | 10. Work Unit No. (TRAIS) |
| | | 11. Contract or Grant No. DOT-FA69WA-2066-MOD 16 |
| 12. Sponsoring Agency Name and Address U.S. Department of Transportation, Federal Aviation Administration, Systems Research and Development Service, Washington, D.C. 20590 | | 13. Type of Report and Period Covered Interim Report |
| | | 14. Sponsoring Agency Code |
| 15. Supplementary Notes | | |

16. Abstract

An index and bibliography are presented covering all ILS and VOR R and D work performed at Ohio University and reported in 19 major technical reports over the years 1965-75.

| | |
|---|---|
| 17. Key Words Instrument Landing System, VHF Omnidirectional Range, ILS/VOR Index, Ohio University | 18. Distribution Statement Document is available to the public through the National Technical Information Service, Springfield, Virginia 22161. |

| 19. Security Classif. (of this report) | 20. Security Classif. (of this page) | 21. No. of Pages | 22. Price |
|---|---|---|---|
| Unclassified | Unclassified | 36 | |

Form DOT F 1700.7 (8-72) Reproduction of completed page authorized

This index has been prepared to aid principally those working with ILS technology, theory and practice. For slightly over one decade Ohio University has been performing engineering research and development on many aspects of the ILS and the results of this work have been documented in 17 reports. This index allows the investigator to identify the reports which cover specific topical items and permits an entry to bibliographical cross references.

The following RD reports are included in this index:

"Instrument Landing System Improvement Program: Far-Field Monitoring," FAA Report Number RD-75-201, Report EER 5-21, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, January, 1975.

"Instrument Landing System Improvement Program," Final Report, FAA Report Number RD-74-214, Report EER 5-20, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, December, 1974.

Garrett, Patrick H. and Robert A. Rondini, "Instrument Landing System Improvement Program: Centerline Monitor," FAA Report Number RD-74-89, Report EER 5-16, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, May, 1974.

McFarland, Richard H., "Investigations to Provide Improved Glide Slope Operation During Periods of Ground-Plane Snow Cover," Volume I - Summary and Conclusions, FAA Report Number RD-74-69,I, Report EER 5-17, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, April, 1974.

Battistelli, J. J. and R. H. McFarland, "Investigations to Provide Improved Glide Slope Operation During Periods of Ground-Plane Snow Cover," Volume II - Details of 1972-1973 Investigations, FAA Report Number RD-74-69, II, Report EER 5-18, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, April, 1974.

Kennedy, William E. and Richard H. McFarland, "Instrument Landing System Improvement Program, Environmental Study of the 200 Foot Aperture Slotted Cable Localizer Antenna Array," FAA Report Number RD-74-94, Report EER 5-19, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, April, 1974.

Rondini, Robert A. and Richard H. McFarland, "Experimental Validation of Boeing 747 ILS Signal Scattering Calculations for Critical Area Determination," Final Report, FAA Report Number RD-74-57, Report EER 18-1, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, January, 1974.

"Instrument Landing System Improvement Program," Fourth Interim Report, FAA Report Number RD-73-137, Report EER 5-15, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, May, 1973.

Stefanik, Michael J., "Gradient Clearance Monitor," Final Report, FAA Report Number RD-72-147, EER 5-14, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, October, 1972.

Morehart, Jack B., R. H. McFarland and David C. Hildebrand, "Snow Effects on Image Glide Path Systems, Winter of 1971-1972," FAA Report Number RD-72-85, Report EER 5-13, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, July, 1972.

"Instrument Landing System Improvement Program," Third Interim Report, FAA Report Number RD-72-71, Report EER 5-12, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, June, 1972.

"Instrument Landing System Improvement Program," Interim Report, FAA Report Number RD-71-30, Report EER 5-11, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, October, 1971.

"Instrument Landing System Improvement Program," Interim Report, FAA Report Number RD-70-9, Report EER 5-10, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, January, 1970.

McFarland, Richard H., Fred Kiko, and G. E. Smith, "VOR Propagation and Stability Study," Final Report, FAA Report Number RD-69-44, Report EER 11-3, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, January, 1970.

"Radio Theodolite Placement Criteria for Glide Path Measurement," Final Report, FAA Report Number RD-69-4, Report EER 20-1, Avionics Engineering Center, Department of Electrical Engineering, Ohio University, Athens, Ohio, January, 1969.

"Earth Cover and Contour Effects on Image Glide Paths, Phase III," Final Report, FAA Report Number RD-68-60,I, Report EER 5-7, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, September, 1968.

McFarland, Richard H., James T. Gorman, and Ted A. Gutwein, "VOR Propagation and Stability Study," FAA Report Number RD-66-92, Report EER 11-1, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, November, 1966.

McFarland, Richard H., J. T. Gorman, D. A. Hill, D. Luttermoser, and D. Miller, "Earth Cover and Contour Effects on Image Glide Paths, Phase II," FAA Report Number RD 66-39, Report EER 5-5, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, July, 1966.

"Earth Cover and Contour Effects on Image Glide Paths," Final Report, FAA Report Number RD-65-30, Report EER 5-1, Avionics Research Group, Department of Electrical Engineering, Ohio University, Athens, Ohio, May 21, 1965.

| | FAA RD REPORT | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Admittance, input | | TM-26, p. 9 |
| mutual | RD 72-71, p. 211 | TM-26, p. 10 |
| Admittance parameters | RD 71-30, p. 38 | |
| Aircraft, interfering | RD 69-44, p. 124 | |
| Aircraft, large, effects of | RD 74-57, p. 1 | |
| Airports, Category II | | TM-34, p. 16 |
| Miami International | RD 74-57, p. 24 | |
| Alarm condition | RD 68-60, p. 7 | |
| Alarm disable relay | | TM-47, p. 9 |
| Alarm, environmental | RD 70-9, p. 76 | |
| false | RD 68-60, pp. 25, 36, 44 | |
| nuisance | | TM-13, p. 12 |
| path | | TM-23, p. 8 |
| power reduction | RD 68-60, p. 26 | |
| tilt switch | RD 74-69,I, p.2 | |
| twin wire monitor | | TM-17, p. 5 |
| Albany test site | RD 74-214, p. 58 | |
| Amplifier, log | | TM-51, p. 4 |
| Amplitude modulation | RD 69-44, p. 188 | |
| Amplitude shaping | RD 73-137, p. 51 | TM-44, pp. 5, 11 |
| Analog, direct | | TM-39, p. 1 |
| Angle change | RD 68-60, p. 71 | |
| Angle dependent signal | | TM-51, p. 4 |
| Angle, elevation | RD 72-71, pp. 24, 35, 177 | TM-27, p. 1 |
| | | TM-20, p. 12 |
| | RD 68-60, p. 112 | |
| | RD 69-44, p. 140 | |
| glide path | RD 72-71, p. 158 | TM-14, p. 2 |
| | RD 70-9, p. 98 | TM-50, p. 4 |
| | RD 68-60, p. 7 | |
| change in | RD 73-137, p. 137 | TM-18, p. 27 |
| | RD 68-60, p. 84 | |
| depressed | RD 72-71, p. 30 | |
| far-field | RD 74-69,I, p. 2 | |
| | RD 73-137, p. 137 | |
| | RD 72-71, pp. 152, 159, 164 | |
| measured | | TM-4, p. 2 |
| theoretical | RD 73-137, p. 82 | |
| incidence | RD 72-71, p. 136 | TM-13, pp. 10, 12 |
| | | TM-18, p. 6 |
| | | TM-41, p. 8 |
| | | TM-42, p. 5 |
| increase | RD 68-60, p. 75 | |
| minimum number | | TM-40, p. 7 |

| | FAA RD REPORT | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Angle, (continued) | | |
| optical reflection | | TM-2, p. 4 |
| scattering | | TM-48, p. 12 |
| sensor | | TM-51, p. 6 |
| Angular, accuracy | | TM-51, p. 2 |
| deviations | | TM-51, p. 4 |
| form factor | RD 73-137, p. 19 | TM-39, p. 2 |
| measurement errors | | TM-31A, p. 5 |
| sensitivity | | TM-45, p. 7 |
| Antenna, collinear directional | | |
| glide slope | RD 74-214, p. 5 | |
| configuration | RD 69-44, p. 17 | |
| current | RD 73-137, p. 63 | TM-35, p. 2 |
| decoupling | | TM-37, p. 4 |
| dephased upper | RD 73-137, p. 73 | |
| directional | RD 65-30, p. 33 | TM-24, p. 1 |
| | | TM-27, p. 1 |
| glide path | RD 72-71, pp. 84, 93 | |
| overflight | RD 73-137, p. 209 | TM-47, p. 2 |
| environment | RD 70-9, p. 60 | |
| excitation | | TM-18, p. 3 |
| faults | | TM-1, p. 1 |
| glide path | | TM-19, p. 8 |
| height | | TM-31A, p. 13 |
| | | TM-41, p. 20 |
| | | TM-50, p. 2 |
| changes | RD 75-201, p. 30 | |
| glide slope | RD 74-214, p. 46 | |
| image | | TM-46, p. 5 |
| induced voltage | | TM-34, p. 30 |
| monitor | RD 72-71, p. 227 | |
| offset | RD 70-9, p. 3 | TM-28, p. 9 |
| | RD 72-71, pp. 182, 189 | |
| | RD 74-214, p. 3 | |
| overflight | RD 74-214, p. 64 | |
| placement of | RD 72-71, p. 9 | |
| ram's horn | RD 69-44, p. 18 | |
| receiving | RD 69-44, p. 68 | |
| induced voltage | | TM-19, p. 33 |
| sideband voltage | | TM-19, p. 34 |
| sideband null | RD 72-71, p. 22 | |
| transmitting | RD 68-60, p. 300 | |
| location | | TM-31A, p. 7 |
| upper | | TM-44, p. 12 |
| Approximation, free space | RD 72-71, p. 182 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Array, capture effect | | TM-20, p. 4 |
| clearance signals | RD 72-71, p. 230 | |
| coefficient | | TM-1, p. 11 |
| colinear, modified | RD 71-30, p. 10 | |
| three dipole | | TM-15, pp. 1, 2 |
| three element | RD 73-137, p. 37 | TM-35, p. 5 |
| configurations | | TM-36, p. 5 |
| directional | RD 68-60, p. 138 | TM-34, p. 12 |
| | RD 73-137, p. 15 | |
| end-fire | RD 70-9, p. 76 | TM-1, p. 14 |
| factor | RD 70-9, pp. 67, 70, 75 | TM-1, pp. 8, 10 |
| | | TM-47, p. 2 |
| fourteen element non-image | | TM-20, p. 4 |
| glide slope, modified | | |
| performance | | TM-20, p. 2 |
| sideband reference | | TM-21, p. 1 |
| transmitting | | TM-35, p. 5 |
| localizer, 15 element | RD 72-71, p. 202 | |
| self-clearing | RD 73-137, p. 209 | |
| V-ring | | TM-36, p. 1 |
| | | TM-33, p. 4 |
| modified | | TM-30, p. 1 |
| monitor | | TM-8, p. 4 |
| non-uniformly spaced | RD 72-71, p. 202 | TM-26, p. 2 |
| slotted cable | RD 74-94, p. 1 | |
| Watts slotted cable antenna | RD 74-214, p. 59 | |
| Autocorrelation function | RD 66-92, p. 54 | |
| Automatic Gain Control (AGC) | RD 75-201, p. 25 | TM-45, p. 21 |
| oscillations | RD 69-44, p. 137 | |
| Automatic Radio Telemetering Theodolite (ARTT) | RD 73-137, p. 95 | TM-45, p. 1 |
| | RD 74-214, pp. 1, 23, 31 | |
| dynamic | RD 74-214, p. 33 | |
| static | | TM-51, p. 24 |
| Azimuth pattern | RD 70-9, p. 81 | TM-5, p. 1 |
| Bandpass, characteristics | RD 72-71, p. 235 | |
| filter | RD 69-44, p. 210 | TM-22, p. 5 |
| receiver characteristics | | TM-33, p. 9 |
| Bandwidth, localizer integral monitor | | TM-37, p. 1 |
| monitor | RD 73-137, p. 200 | |
| Barometric pressure | RD 69-44, p. 38 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Beam, azimuth | | TM-15, p. 2 |
| elevation | | TM-15, p. 2 |
| switching | RD 74-214, p. 85 | |
| width | | TM-45, p. 3 |
| Bearing, error | RD 69-44, pp. 30, 120 | |
| stability | RD 66-92, p. 27 | |
| Bend, downward | | TM-14, p. 13 |
| Bendix, RNA 26-C | RD 69-44, p. 208 | |
| Bird effects | RD 73-137, p. 217 | TM-17, p. 9 |
| Blanking signal | | TM-47, p. 2 |
| Boeing 747, parked | | TM-19, p. 46 |
| taxiing | | TM-19, p. 37 |
| Broadband characteristics | RD 72-71, p. 225 | TM-36, p. 6 |
| Calibration procedure | RD 68-60, p. 229 | |
| Cancellation, low-angle | RD 65-30, p. 31 | |
| Capture area, effective | | TM-41, p. 12 |
| Capture effect | RD 73-137, p. 64 | |
| | RD 74-214, p. 1 | |
| ground plane reduction | | TM-20, p. 5 |
| sideband signal | | TM-20, p. 15 |
| signal strength | | TM-20, p. 12 |
| system | RD 65-30, p. 31 | |
| | RD 68-60, p. 208 | |
| | RD 72-71, pp. 38, 40 | |
| Carrier, amplitudes | RD 72-71, p. 207 | TM-26, p. 5 |
| pattern | RD 72-71, pp. 202, 205 | TM-41, p. 16 |
| | | TM-26, pp. 1, 5 |
| | | TM-20, p. 4 |
| sideband signal | | TM-19, p. 34 |
| Carrier and sideband patterns | | TM-21, p. 1 |
| Category II, airports | | TM-34, p. 16 |
| flyability | RD 72-71, p. 14 | |
| glide path | | TM-31A, p. 4 |
| tolerances | RD 69-4, p. 3 | TM-14, p. 10 |
| Centerline, ground measurements | | TM-48, p. 54 |
| runway | RD 74-89, p. 42 | |
| Chopper amplifier | RD 73-137, p. 264 | TM-39, pp. 7, 9 |
| Christoffel symbols | | TM-34, p. 26 |
| Circuit, average value | RD 74-89, p. 26 | |
| precision average value | RD 74-89, p. 40 | |
| summing | | TM-51, p. 6 |
| Circuitry, angle and sum | | TM-51, p. 12 |
| LED/photoresistor | | TM-51, p. 12 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Clearance | | TM-40, pp. 3, 7 |
| array signals | | TM-33, p. 2 |
| below path | RD 70-9, p. 12 | |
| far field | | TM-40, p.7 |
| localizer | RD 73-137, p. 197 | TM-26, p. 1 |
| minimum | | TM-26, p. 19 |
| predictions | | TM-13, p. 5 |
| radio frequency (RFC) | RD 75-201, p. 22 | |
| region | | TM-9, p. 6 |
| signal | | TM-9, p. 1 |
| symmetry | | TM-33, p. 18 |
| Cockpit indicator deflection | | TM-19, p. 35 |
| Cold front | RD 66-92, p. 89 | |
| Computer program | RD 70-9, p. 54 | |
| | RD 68-60, p. 111 | |
| glide path | RD 65-30, p. 23 | |
| Computer routine | | TM-41, p. 2 |
| Confidence factor | | TM-34, p. 17 |
| Contour, CDI | RD 74-57, p. 9 | TM-42, p. 5 |
| earth | RD 65-30, p. 3 | |
| effects | RD 66-39, pp. 28, 44 | |
| on image glide path | RD 68-60, p. 94 | |
| glide slope | RD 74-57, p. 21 | |
| irregular | RD 65-30, p. 23 | |
| lines | RD 68-60, p. 309 | |
| map | | TM-14, p. 13 |
| | | TM-41, p. 18 |
| localizer | RD 74-57, p. 17 | |
| perturbation | RD 74-214, p. 82 | |
| reflection | RD 74-57, p. 6 | |
| uniformity | RD 65-30, p. 9 | |
| Coordinates, cartesian | | TM-34, p. 37 |
| circular cylindrical | RD 70-9, p. 41 | |
| cylindrical | | TM-34, p. 37 |
| rectangular | | TM-48, p. 12 |
| systems | RD 73-137, p. 250 | TM-46, pp. 9, 10 |
| | RD 74-214, p. 163 | TM-31A, p. 6 |
| | | TM-34, p. 34 |
| | | TM-52, p. 5 |
| relationships | | TM-48, p. 56 |
| transformation | | TM-48, p. 24 |
| Corner reflector aperture | | TM-15, p. 11 |
| Counter poise | RD 66-39, p. 96 | |
| Coupling, end | RD 71-30, p. 11 | TM-15, p. 5 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Course aberrations | | TM-29, p. 10 |
| alignment and clearances | | TM-33, p. 17 |
| bends | RD 74-57, pp. 9, 17, 21, 30 | TM-48-R, pp. 1, 30 |
| | RD 74-214, p. 134 | TM-24, p. 1 |
| Course Deviation Indicator (CDI) | RD 75-201, p. 1 | TM-41, pp. 2, 17 |
| | | TM-48, p. 28 |
| | | TM-52, p. 8 |
| contour | RD 74-57, p. 9 | TM-42, p. 5 |
| deflections | | TM-34, p. 4 |
| deviations | RD 69-44, p. 38 | |
| diurnal drift | RD 66-92, p. 94 | |
| dynamic | RD 74-89, p. 9 | TM-41, p. 18 |
| | RD 73-137, pp. 158, 166 | TM-42, pp. 1, 5 |
| | RD 74-89, p. 11 | TM-52, p. 8 |
| errors | RD 69-44, pp. 14, 28, 156 | |
| filtered output | RD 73-137, p. 249 | |
| noise | RD 69-44, pp. 37, 209 | |
| oscillations | RD 69-44, pp. 94, 156 | |
| peak regions | RD 73-137, p. 171 | |
| perturbation | RD 69-44, p. 207 | |
| type | RD 69-44, p. 32 | |
| response | RD 69-44, p. 68 | |
| static | | TM-42, p. 7 |
| step functions | RD 66-92, p. 94 | |
| Course deviations | | TM-51, p. 21 |
| far field | RD 74-94, p. 4 | |
| maximum | RD 69-44, p. 59 | |
| Course errors | RD 69-44, pp. 5, 103, 133 | |
| Course, glide slope structure | RD 74-57, p. 43 | |
| oscillation | RD 69-44, p. 37 | |
| perturbations | RD 69-44, p. 206 | TM-52, p. 9 |
| position tolerance | RD 74-89, p. 46 | |
| roughness | RD 74-89, p. 9 | |
| shifts | RD 69-44, p. 37 | |
| structure | | TM-9, p. 2 |
| Critical area | RD 70-9, pp. 18, 34 | TM-34, p. 1 |
| | RD 72-71, p. 93 | TM-48, p. 1 |
| | RD 73-137, pp. 5, 8 | |
| | RD 74-89, p. 3 | |
| | RD 74-214, p. 11 | |
| Category III | | TM-48, p. 34 |
| glide slope | RD 74-57, p. 5 | |
| | RD 74-214, p. 31 | |
| localizer | RD 73-137, p. 165 | TM-48, p. 54 |
| | RD 74-57, p. 8 | |
| | RD 74-214, pp. 17, 62, 79 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Critical area (continued) | | |
| localizer | | |
| Category III | RD 74-214, p. 127 | |
| worst case | RD 74-57, p. 1 | |
| Cross-talk | RD 72-71, p. 251 | TM-33, p. 17 |
| Current, antenna | RD 73-137, p. 63 | TM-35, p. 2 |
| carrier | RD 71-30, p. 35 | TM-9, pp. 2, 3 |
| center element | RD 71-30, p. 41 | |
| distribution | RD 70-9, p. 30 | |
| dark | | TM-51, p. 4 |
| distribution | | TM-26, p. 11 |
| fuselage surface | | TM-19, p. 18 |
| measured array | | TM-43, p. 16 |
| parasitic | RD 73-137, p. 179 | TM-36, p. 11 |
| sheet | RD 72-71, p. 75 | TM-19, p. 27 |
| theoretically correct antenna | | TM-43, p. 5 |
| Cylinder-trapezoid (C-T) approximation | | TM-52, p. 1 |
| Dark current | RD 74-214, p. 182 | |
| Data extraction | RD 69-44, p. 33 | |
| Demodulation, FM | RD 69-44, p. 212 | |
| Dephasing, SB | RD 72-71, p. 189 | TM-28, p. 4 |
| Derogation, maximum | | TM-42, p. 7 |
| | | TM-41, p. 19 |
| signal | | TM-48, p. 19 |
| Detector, coherent | | TM-22, p. 7 |
| envelope | | TM-22, p. 3 |
| envelope and coherent | RD 72-71, p. 227 | |
| photocell | | TM-51, p. 1 |
| photo-sensitive | | TM-47, p. 13 |
| Dielectric constant | RD 69-44, p. 8 | TM-13, p. 4 |
| | RD 65-30, p. 13 | |
| | RD 66-39, pp. 10, 20 | |
| | RD 68-60, p. 8 | |
| | RD 74-214, p. 3 | |
| complex | RD 66-39, p. 81 | |
| earth | RD 68-60, p. 17 | |
| snow | RD 68-60, pp. 16, 25, 65, 205 | TM-18, p. 7 |
| | RD 72-85, p. 13 | |
| | RD 66-39, p. 15 | |
| soil | RD 68-60, p. 60 | |
| | RD 65-30, p. 62 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Difference in Depth Modulation (DDM) | RD 65-30, pp. 23, 45 | TM-7, p. 7 |
| | RD 66-39, pp. 25, 95 | TM-11, pp. 2, 4 |
| | RD 68-60, pp. 15, 22 | TM-18, pp. 3, 8, 13 |
| | RD 70-9, p. 25 | TM-20, p. 5 |
| | RD 71-30, p. 58 | TM-26, p. 5 |
| | RD 72-147, pp. 18, 22, 27, 34 | TM-28, p. 1 |
| | | TM-41, p. 17 |
| | RD 72-71, pp. 83, 128, 135 | TM-43, p. 2 |
| | | TM-48, p. 28 |
| | RD 73-137, p. 157 | TM-52, p. 8 |
| | RD 74-214, p. 123 | |
| | RD 75-201, p. 21 | |
| below path | RD 71-30, p. 34 | |
| calculation for capture effect | RD 65-30, p. 79 | |
| calculation for null reference | RD 65-30, p. 76 | |
| change | RD 68-60, p. 22 | |
| clearance | | TM-9, p. 16 |
| disturbance | | TM-2, p. 2 |
| far-field expressions | RD 72-147, p. 33 | |
| fluctuation | | TM-9, p. 19 |
| indication change | RD 68-60, p. 57 | |
| orbital measurements | | TM-26, p. 15 |
| worst case | RD 72-71, p. 140 | TM-18, p. 19 |
| zero | RD 74-89, p. 12 | TM-46, p. 25 |
| height | RD 73-137, pp. 128, 135 | |
| line | RD 72-71, p. 16 | |
| Difference frequency | RD 75-201, p. 25 | |
| Diffracted field | | TM-48, p. 5 |
| Diffracted signal | RD 66-92, p. 94 | |
| Diffraction effects | RD 73-137, p. 147 | |
| | RD 74-89, pp. 6, 11 | |
| Diffraction model | RD 74-89, pp. 4, 5 | |
| Digital circuit design | RD 69-44, p. 212 | |
| Direct analog | | TM-44, p. 12 |
| scale model | RD 73-137, p. 55 | |
| Direct sideband field | RD 70-9, p. 25 | |
| Direct sideband voltage | RD 70-9, p. 52 | |
| | RD 72-71, p. 81 | |
| Direct signal | RD 66-92, p. 87 | |
| | RD 69-44, p. 208 | |
| Directional antennas | RD 65-30, p. 33 | TM-24, p. 1 |
| | | TM-27, p. 1 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Directional arrays | RD 68-60, p. 138 | TM-34, p. 12 |
| | RD 73-137, p. 15 | |
| Directive horizontal pattern | | TM-19, p. 46 |
| Discontinuities, effects in the | | |
| reflecting surface | RD 73-137, p. 5 | TM-34, p. 1 |
| Distortion | | TM-33, p. 19 |
| modulator bridge | RD 72-71, p. 230 | |
| | RD 74-214, p. 18 | |
| modulator output waveform | | TM-33, p. 2 |
| Distribution network | RD 73-137, p. 190 | |
| Disturbance of fuselage plus | | |
| tailfin | RD 71-30, p. 75 | |
| Doppler effects | RD 66-39, p. 44 | |
| localizer | RD 72-71, p. 303 | TM-22, p. 1 |
| shift | RD 66-39. p. 36 | |
| | RD 66-92, p. 33 | TM-22, p. 1 |
| VOR | RD 69-44, p. 211 | |
| Drainage in near field | RD 68-60, p. 86 | |
| Duct, tropospheric | RD 69-44, pp. 12, 103 | |
| Ducting | RD 69-44, pp. 157, 207 | |
| Dynamic CDI | RD 74-89, pp. 9, 11 | TM-41, p. 18 |
| | RD 73-137, pp. 158, 166 | TM-42, pp. 1, 5 |
| | | TM-52, p. 8 |
| Earth moving | RD 68-60, p. 209 | |
| Electric field | RD 72-71, p. 62 | TM-19, p. 2 |
| | | TM-32, p. 2 |
| | | TM-48, p. 25 |
| computation | RD 72-71, p. 231 | |
| incident | RD 70-9, pp. 37, 41 | TM-6, p. 2 |
| | RD 72-71, p. 50 | TM-34, p. 21 |
| polarized | | TM-19, p. 28 |
| re-radiated | RD 72-71, p. 75 | TM-19, pp. 28, 33 |
| scattered | RD 72-71, p. 72 | TM-19, p. 25 |
| | RD 74-214, p. 116 | TM-48, p. 22 |
| | | TM-52, p. 7 |
| sideband | | TM-2, p. 3 |
| space, in | RD 66-39, p. 3 | |
| vertical component | RD 68-60, p. 111 | |
| vertically polarized | RD 72-71, p. 76 | |
| Elevation angle | RD 72-71, pp. 24, 35, 177 | TM-27, p. 1 |
| | | TM-20, p. 12 |
| | RD 68-60, p. 112 | |
| | RD 69-44, p. 140 | |
| End-fire array | RD 70-9, p. 76 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Environmental changes | | TM-47, p. 4 |
| effect on path | RD 74-214, p. 57 | |
| Environmental data | RD 74-69, II, p. 8 | |
| effects | | TM-17, p. 11 |
| Environmental disturbances | RD 75-201, p. 20 | |
| Error, simulated | RD 69-44, p. 172 | |
| Fading characteristic | RD 66-92, p. 73 | |
| Far-field, angular position | RD 68-60, p. 205 | |
| centerline prediction | RD 70-9, p. 66 | |
| conditions | | TM-50, p. 10 |
| path angle | RD 74-69, I, p. 2 | |
| radiation signal | | TM-50, p. 1 |
| representation of conditions | | TM-35, p. 9 |
| sideband and carrier contributions | | TM-11, p. 2 |
| signals | RD 70-9, p. 56 | TM-1, p. 4 |
| tolerance limits | | TM-13, p. 11 |
| worst case | | TM-18, p. 13 |
| Faults | | TM-50, p. 1 |
| antenna | | TM-1, p. 1 |
| antenna height change | RD 72-147, p. 53 | |
| attenuation | | TM-50, p. 16 |
| classes of | RD 70-9, p. 88 | |
| | RD 72-71, p. 221 | |
| controlled system experiments | RD 72-147, p. 47 | |
| facility | RD 72-147, p. 2 | |
| glide path monitor | | TM-35, p. 16 |
| indications | | TM-44, p. 12 |
| integral monitor | | TM-30, p. 2 |
| list | RD 72-71, p. 166 | |
| localizer | | TM-7, p. 2 |
| localizer | RD 73-137, p. 206 | TM-11, p. 5 |
| | | TM-30, p. 1 |
| | | TM-37, p. 4 |
| monitor and far-field responses | RD 71-30, p. 91 | |
| monitor type matrix | RD 71-30, p. 173 | |
| 90° | | TM-40, p. 3 |
| sideband phase | RD 74-214, p. 58 | |
| | RD 75-201, p. 15 | |
| sideband power amplitude | RD 74-214, p. 58 | |
| tests | RD 70-9, p. 81 | TM-35, p. 1 |
| | RD 73-137, p. 41 | TM-50, p. 10 |
| | RD 74-214, pp. 51, 57 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Feedback | | TM-37, p. 1 |
| Feeder length | | TM-26, p. 11 |
| Field strength | RD 69-44, p. 221 | |
| | RD 72-71, pp. 33, 232 | |
| electromagnetic | | TM-39, p. 3 |
| far-field electric | | TM-33, p. 3 |
| reflected sideband | | TM-41, p. 12 |
| from fuselage | RD 73-137, p. 156 | |
| from tailfin | RD 73-137, p. 153 | |
| relative | | TM-33, pp. 4, 6 |
| Field, total | RD 68-60, p. 14 | TM-18, p. 7 |
| | | TM-33, p. 4 |
| | | TM-48, p. 27 |
| Figure of merit | | TM-21, p. 1 |
| | | TM-20, p. 12 |
| Filtering | RD 69-44, p. 195 | |
| Filters, bandpass | RD 69-44, p. 210 | TM-22, p. 5 |
| infrared | | TM-45, p. 11 |
| receiver | RD 74-89, p. 23 | |
| Flag, current | | TM-23, p. 5 |
| Flare tolerance | RD 69-4, p. 1 | |
| Flight checks | | TM-34, pp. 14, 16 |
| | | TM-41, p. 20 |
| Flight path, aircraft | | TM-19, p. 18 |
| Flight systems, automatic | RD 71-30, p. 21 | |
| Flight test | | TM-40, p. 1 |
| | | TM-43, pp. 1, 5 |
| Flux density, luminous | | TM-51, p. 2 |
| Flyability | RD 68-60, p. 117 | |
| Fly down | RD 71-30, p. 30 | TM-14, p. 5 |
| | | TM-4, p. 10 |
| Fly up | | TM-21, p. 6 |
| Foilage attenuation | RD 68-60, pp. 144, 232 | |
| Foilage effect | RD 68-60, p. 158 | |
| Form factor, angular | RD 73-137, p. 19 | TM-39, p. 2 |
| Fraunhofer diffraction theory | RD 74-214, p. 11 | |
| Free space approximation | | TM-28, p. 4 |
| Frequency, change | RD 69-44, p. 33 | |
| difference | RD 69-44, p. 193 | |
| line change | RD 66-92, pp. 27, 92 | |
| of oscillation | RD 68-60, p. 114 | |
| scalloping | RD 70-9, p. 63 | TM-1, p. 3 |
| | RD 69-44, p. 16 | TM-41, p. 17 |
| | RD 73-137, p. 170 | TM-42, p. 6 |
| | RD 74-89, p. 6 | |
| shift | RD 72-147, p. 3 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Frequency (Con't.) | | |
| spacial | RD 70-9, p. 69 | TM-32, p. 3 |
| | RD 71-30, p. 62 | |
| | RD 72-71, p. 195 | |
| Fresnel zones | RD 68-60, p. 102 | TM-4, p. 6 |
| | RD 65-30, pp. 5, 26 | |
| | RD 72-147, pp. 2, 66 | |
| | RD 73-137, p. 15 | |
| first | RD 65-30, p. 30 | TM-34, p. 6 |
| | RD 72-147, pp. 5, 54 | |
| integrals | | TM-48, pp. 16, 20 |
| | | TM-52, p. 6 |
| reflection coefficient | RD 65-30, p. 29 | |
| Front, vertical | RD 69-44, p. 157 | |
| zeroth | RD 69-44, p. 11 | |
| Fuselage | | TM-19, pp. 1, 9 |
| center | | TM-19, p. 50 |
| radius | | TM-19, p. 15 |
| reflected field | RD 73-137, p. 156 | TM-41, p. 15 |
| signals reflected from | RD 73-137, p. 153 | TM-41, p. 12 |
| | RD 71-30, p. 63 | |
| Gain, open loop | | TM-45, p. 19 |
| sensor | | TM-45, p. 11 |
| Geometry | RD 72-71, p. 84 | TM-19, p. 46 |
| conical | RD 72-147, p. 4 | |
| problem | | TM-31A, p. 1 |
| reflection | | TM-42, p. 1 |
| Glide Slope (Glide Path, Path, GP, GS) | | TM-49, p. 1 |
| acceptability | RD 72-71, p. 14 | |
| adjustment | | TM-3, p. 1 |
| alarm | | TM-23, p. 8 |
| angle | RD 68-60, pp. 164, 205 | TM-46, pp. 3, 9 |
| | RD 66-39, pp. 8, 43 | TM-35, p. 9 |
| displacement | | TM-23, p. 1 |
| far field | | TM-23, pp. 2, 12 |
| measured | | TM-23, p. 8 |
| | | TM-4, p. 2 |
| array | | TM-20, p. 2 |
| | | TM-21, p. 1 |
| | | TM-35, p. 5 |
| Atlanta | RD 72-71, p. 3 | |
| | RD 69-4, p. 3 | |
| Australian | | TM-29, p. 6 |
| calculated | | TM-14, p. 2 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Glide Slope (Con't.) | | |
| capture effect | RD 68-60, p. 158 | TM-28, p. 1 |
| | RD 72-147, p. 62 | TM-43, p. 1 |
| | RD 72-71, p. 182 | |
| | RD 74-214, p. 8 | |
| capture monitor | RD 75-201, p. 24 | |
| Category II, flyable | | TM-31A, p. 4 |
| Charleston, W. Va. | RD 66-39, p. 26 | TM-29, p. 11 |
| | | TM-43, p. 14 |
| clearance | RD 73-137, p. 64 | TM-43, p. 6 |
| | RD 72-147, pp. 1, 5 | |
| computed performance | | TM-20, p. 1 |
| computer program | RD 65-30, p. 23 | |
| conditions | | TM-13, p. 9 |
| corrections, open loop | RD 68-60, p. 206 | |
| course structure | RD 74-57, p. 43 | TM-52, p. 1 |
| course width | RD 74-57, p. 62 | |
| curvature | RD 68-60, p. 140 | |
| Denver | RD 71-30, p. 30 | |
| derogation | RD 74-214, p. 11 | |
| effects | RD 73-137, pp. 141, 165 | TM-41, p. 1 |
| Detroit | RD 73-137, p. 76 | |
| | RD 72-71, p. 30 | |
| diffraction | | TM-52, p. 2 |
| displacement | RD 70-9, pp. 53, 108 | TM-3, p. 3 |
| | | TM-6, p. 16 |
| electronically reshaped | | TM-4, p. 6 |
| FAA installation procedures | | TM-43, p. 14 |
| far field | RD 72-85, p. 1 | |
| | RD 68-60, p. 89 | |
| flare | RD 73-137, p. 76 | |
| Flint, Michigan | RD 66-39, p. 8 | |
| flyability | | TM-27, p. 2 |
| foilage effects | RD 66-39, p. 44 | |
| image | RD 65-30, p. 1 | TM-46, p. 1 |
| inverted | RD 72-71, pp. 40, 131 | TM-18, p. 5 |
| L-band | RD 72-71, p. 201 | |
| lowered | | TM-20, p. 15 |
| mathematical model | RD 68-60, p. 6 | TM-18, p. 1 |
| | RD 66-39, p. 43 | |
| measured | | TM-14, p. 2 |
| modified sideband reference | RD 68-60, p. 148 | |
| modifying shape | | TM-4, p. 11 |
| Monterey, California | RD 71-30, p. 30 | TM-29, pp. 1, 6 |
| | RD 72-71, p. 38 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Glide Slope (Con't.) | | |
| narrow | | TM-23, p. 10 |
| non-uniform horizontal structure | RD 68-60, p. 187 | |
| null reference | RD 68-60, p. 6 | TM-43, pp. 1, 14 |
| | RD 72-147, p. 58 | |
| Oakland | RD 70-9, p. 95 | |
| Ohio University | RD 66-39, p. 28 | |
| oscillation | RD 68-60, p. 172 | |
| frequency | RD 68-60, p. 140 | |
| out-of-tolerance | RD 68-60, p. 86 | |
| outages | | TM-13, p. 9 |
| Pittsburgh | RD 73-137, p. 86 | |
| | RD 72-71, p. 49 | |
| | RD 71-30, p. 25 | |
| | RD 66-39, p. 25 | |
| null-reference | RD 66-39, p. 34 | |
| roughness | RD 68-60, p. 134 | |
| position | RD 70-9, p. 12 | |
| radiation patterns | RD 72-71, p. 247 | |
| receiver calibration | RD 75-201, p. 3 | TM-23, p. 6 |
| reference | | TM-14, p. 11 |
| | | TM-31A, p. 1 |
| path in space | RD 72-71, p. 20 | |
| representation | | TM-18, p. 4 |
| roughness | RD 68-60, p. 197 | TM-24, p. 1 |
| due to terrain | RD 68-60, p. 207 | |
| San Francisco | RD 70-9, p. 98 | TM-31A, p. 3 |
| | | TM-4, p. 1 |
| shape | | TM-31A, p. 6 |
| sideband image signal | | TM-3, p. 1 |
| sideband reference | RD 70-9, p. 101 | TM-50, p. 10 |
| | RD 72-147, p. 60 | |
| | RD 74-214, p. 45 | |
| site irregularities | RD 72-147, p. 45 | |
| sites | | TM-29, p. 6 |
| softening | RD 70-9, p. 110 | |
| straight line | RD 70-9, p. 101 | TM-4, p. 6 |
| straightness | RD 74-214, p. 1 | |
| structure, nonlinearity | RD 68-60, p. 138 | |
| vertical | RD 74-57, p. 44 | |
| | RD 68-60, p. 94 | |
| 3 decibel | | TM-50, p. 4 |
| 3-dimensional properties | RD 68-60, p. 190 | |
| tolerances, lower limit | | TM-4, p. 10 |
| transmitting site location | | TM-31A, p. 5 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Glide Slope (Con't.) | | |
| Travis AFB | RD 72-71, p. 27 | TM-31A, p. 10 |
| | RD 73-137, p. 128 | |
| width | RD 68-60, p. 144 | TM-33, p. 23 |
| Gradients, horizontal | RD 69-44, p. 8 | |
| Grading | RD 72-71, pp. 12, 15 | TM-14, pp. 2, 8 |
| criteria | RD 71-30, p. 26 | |
| | RD 74-214, p. 4 | |
| non-standard terrain | RD 74-214, p. 21 | |
| requirement | | TM-8, p. 4 |
| runway | | TM-31A, p. 13 |
| terrain | RD 68-60, p. 173 | |
| | RD 71-30, p. 3 | |
| Graphical techniques | RD 65-30, p. 35 | |
| Ground clearance monitor | RD 72-147, pp. 1, 37 | |
| | RD 74-69, II, p. 49 | |
| Ground coverings | RD 65-30, pp. 2, 17 | |
| Ground elevation, constant rate of change | | TM-12, p. 2 |
| Ground illumination | RD 72-71, p. 170 | |
| irregular | RD 73-137, p. 126 | TM-46, p. 15 |
| slope | | TM-46, p. 14 |
| theory, truncated | RD 73-137, p. 73 | |
| traffic procedures | RD 74-89, p. 11 | |
| variations | | TM-46, p. 3 |
| Ground Plane | RD 72-71, p. 40 | |
| | RD 65-30, p. 2 | |
| conductivity of | RD 68-60, p. 89 | |
| discontinuities in near field | RD 73-137, p. 114 | TM-46, p. 1 |
| effect | | TM-13, p. 10 |
| effective | RD 68-60, p. 131 | |
| elevated | RD 73-137, p. 140 | |
| extended | | TM-32, p. 1 |
| | | TM-29, p. 3 |
| extension | RD 74-214, p. 5 | |
| fourteen element array | | TM-20, p. 12 |
| height | RD 75-201, p. 30 | |
| idealized | | TM-20, p. 1 |
| length | | TM-21, p. 1 |
| limited | RD 73-137, p. 60 | TM-28, p. 1 |
| long | RD 72-71, p. 177 | |
| near field | RD 68-60, p. 209 | |
| parallel wire | RD 72-71, p. 193 | |
| raised | RD 68-60, pp. 17, 25, 57 | |
| | RD 71-30, p. 21 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Ground Plane (Con't.) | | |
| screen | RD 65-30, p. 33 | |
| elevated | RD 73-137, p. 179 | |
| | RD 65-30, p. 19 | |
| variable height | RD 72-71, p. 225 | |
| size | | TM-20, p. 15 |
| truncated | RD 73-137, p. 60 | TM-43, p. 1 |
| | RD 72-71, pp. 38, 170, 259 | TM-29, p. 1 |
| | RD 71-30, pp. 5, 30 | |
| | RD 74-214, p. 4 | |
| wire | RD 72-71, p. 45 | |
| Guidance, rollout | RD 74-89, p. 46 | |
| | RD 74-214, p. 79 | |
| vertical | | TM-34, p. 1 |
| H-field | | TM-48, p. 4 |
| incident | RD 70-9, pp. 37, 42 | TM-6, p. 2 |
| | RD 72-71, pp. 54, 62, 73 | TM-19, pp. 2, 21 |
| scattered | RD 74-214, p. 104 | TM-48, p. 7 |
| | | TM-52, p. 4 |
| tangential components | | TM-19, pp. 12, 15, 26 |
| total | | TM-19, p. 37 |
| Harmonics | RD 72-71, p. 247 | TM-33, p. 6 |
| response to | RD 72-71, p. 235 | |
| Huygen sources | RD 66-39, p. 43 | TM-46, p. 2 |
| Hysterisis, relay | | TM-51, p. 18 |
| IBM results | | TM-41, p. 19 |
| Illuminated region | | TM-48, pp. 6, 7 |
| Illumination function | | TM-8, p. 1 |
| ground | | TM-20, p. 2 |
| low angle scatterers | | TM-20, p. 12 |
| Image antenna | | TM-46, p. 5 |
| location | RD 73-137, pp. 118, 121, 124 | TM-46, pp. 10, 14 |
| intensity | | TM-45, p. 6 |
| localizer field | | TM-2, p. 2 |
| theory | | TM-20, p. 2 |
| Imaging | | TM-19, p. 19 |
| Impedance parameters | | TM-26, p. 10 |
| terminal | | TM-15, p. 6 |
| Impulse function | RD 66-92, pp. 33-38 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Incidence Angle | RD 72-71, p. 136 | TM-42, p. 5 |
| | | TM-13, pp. 10, 12 |
| | | TM-18, p. 6 |
| | | TM-41, p. 8 |
| Incident field | | TM-48, p. 25 |
| cancellation | RD 72-71, p. 62 | TM-19, p. 12 |
| determination | RD 65-30, p. 38 | |
| E and H | | TM-19, p. 7 |
| and scattered | | TM-48, p. 2 |
| Index of refraction | RD 69-44, p. 7 | |
| ILS | RD 74-214, p. 1 | |
| ILS signal reflections, tolerances | RD 71-30, p. 20 | |
| Integration increments | RD 66-39, p. 21 | |
| | RD 68-60, pp. 100, 105 | |
| Interference, adjacent channel | RD 74-214, p. 86 | |
| co-channel | RD 69-44, pp. 161, 181 | |
| Ion density | RD 69-44, p. 160 | |
| Ionization, layer | RD 72-147, p. 3 | |
| Ionospheric effects | RD 69-44, p. 211 | |
| Isolation, combiner | | TM-37, p. 11 |
| Kirchhoff's, integral equation | RD 74-214, p. 101 | |
| scaler equation | | TM-48, p. 3 |
| vector equation | | TM-52, p. 2 |
| LED driver | | TM-51, p. 10 |
| Light flux | | TM-45, p. 3 |
| intensity | | TM-45, pp. 7, 22 |
| Line cutting | RD 73-137, p. 182 | |
| Localizer | RD 74-214, p. 13 | |
| Category III | RD 74-89, p. 2 | |
| | RD 74-214, p. 74 | |
| clearance | RD 73-137, p. 197 | TM-26, p. 1 |
| course integrity | RD 70-9, p. 29 | |
| deviation | RD 74-89, p. 33 | |
| diffraction of signals | | TM-48, p. 2 |
| doppler | RD 72-71, p. 303 | TM-22, p. 1 |
| faults | RD 73-137, p. 206 | TM-11, p. 5 |
| | | TM-30, p. 1 |
| | | TM-37, p. 4 |
| field strength | RD 74-89, p. 18 | |
| 14-element self-clearing | RD 74-214, p. 23 | |
| ILS system | RD 73-137, p. 141 | |
| microampere disturbance of course | | TM-10, p. 9 |
| path width | | TM-16, p. 2 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| pattern | | TM-33, p. 2 |
| | | TM-36, p. 2 |
| ±35° | RD 74-214, p. 14 | |
| precision monitor receiver | RD 74-89, p. 15 | |
| signal derogation | RD 74-89, p. 4 | |
| space pattern | RD 73-137, p. 192 | |
| test site | RD 70-9, p. 29 | |
| two-frequency capture effect | RD 74-214, p. 83 | |
| V-ring array, 15 element | | TM-42, p. 7 |
| vertical pattern | | TM-41, p. 8 |
| Logic circuit | RD 66-92, p. 8 | |
| Logic concepts | | TM-31A, p. 3 |
| Look angle | RD 69-44, pp. 74, 158 | |
| Loop, pickup | RD 70-9, p. 60 | |
| Magnetic field | | TM-48, p. 4 |
| Magnetic vector potential | RD 65-30, p. 36 | |
| Main sideband feeder, phase lead | RD 73-137, p. 64 | TM-29, p. 3 |
| | | TM-43, p. 8 |
| Matching, least squares | RD 72-71, p. 207 | TM-26, p. 2 |
| Mechanical modulator | | TM-33, p. 24 |
| Meteoroid | RD 69-44, p. 209 | |
| Meteoroid activity | RD 69-44, p. 161 | |
| Miami International Airport | RD 74-57, p. 24 | |
| Model, aircraft simplified | | TM-34, p. 3 |
| direct analog scale | RD 73-137, p. 8 | |
| glide path scale | RD 72-147, p. 55 | |
| mathematical | RD 68-60, p. 95 | TM-52, p. 1 |
| | RD 69-44, pp. 3, 207 | TM-46, p. 26 |
| glide slope | RD 66-39, p. 43 | TM-18, p. 1 |
| receiver | | TM-22, p. 3 |
| validation | RD 74-57, p. 5 | TM-46, p. 18 |
| meteorological | RD 66-92, p. 1 | |
| n-front | RD 69-44, p. 9 | |
| parabolic front | RD 69-44, p. 16 | |
| refractive | RD 69-44, p. 12 | |
| scale, Australian | | TM-52, p. 1 |
| direct analog | | TM-34, p. 4 |
| physical | RD 72-71, p. 93 | |
| snow and soil conditions | | TM-13, p. 11 |
| Modulation, amplitude | RD 69-44, p. 188 | |
| frequencies | RD 69-44, p. 12 | |
| low signal | RD 69-44, p. 212 | |
| percent | RD 69-44, p. 187 | |
| propeller | RD 68-60, pp. 108, 158 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Modulator, bridge distortion | RD 72-71, p. 230 | |
| harmonics | RD 72-71, p. 252 | |
| tolerances | RD 72-71, pp. 230, 246 | TM-33, p. 1 |
| mechanical, tolerances | RD 72-71, p. 252 | TM-33, p. 24 |
| Monitor | | TM-40, p. 7 |
| analog | RD 70-9, p. 57 | TM-11, p. 1 |
| | RD 71-30, pp. 24, 58 | TM-44, p. 1 |
| aperture | | TM-1, p. 9 |
| aperture type | | TM-1, p. 6 |
| array coefficients | | TM-8, p. 4 |
| bandwidth | RD 73-137, p. 200 | |
| below path | RD 71-30, p. 34 | |
| clearance | RD 74-214, p. 51 | |
| capture effect probe mechanization | | TM-44, p. 5 |
| centerline aperture | RD 70-9, p. 66 | |
| near field | RD 70-9, pp. 66, 67 | TM-1, pp. 4, 7, 10 |
| clearance | RD 70-9, p. 19 | |
| capture effect glide path | RD 72-147, p. 34 | |
| sideband reference glide path | RD 72-147, p. 33 | |
| course | RD 70-9, p. 81 | |
| environmental | RD 71-30, p. 25 | |
| far field | RD 69-44, p. 23 | |
| | RD 74-214, p. 58 | |
| | RD 75-201, p. 1 | |
| far-field, environmental | RD 72-147, p. 2 | |
| Ohio University site | RD 69-44, p. 5 | |
| faults | RD 71-30, pp. 91, 173 | |
| field received | RD 66-39, p. 8 | |
| fixed point | RD 68-60, p. 64 | |
| frequency changes | RD 73-137, p. 217 | |
| gradient clearance (GCM) | RD 74-69, II, p. 49 | |
| | RD 72-147, pp. 1, 37 | |
| | RD 74-214, p. 51 | |
| | RD 75-201, p. 3 | |
| ground based | RD 69-44, p. 124 | |
| ideal | RD 71-30, p. 50 | TM-5, p. 2 |
| | RD 74-214, p. 15 | TM-11, p. 1 |
| integral | RD 74-94, p. 16 | TM-7, p. 1 |
| | RD 72-85, p. 13 | TM-1, p. 6 |
| | RD 73-137, pp. 41, 90 | |
| | RD 71-30, p. 20 | |
| | RD 70-9, pp. 18, 56 | |
| | RD 74-214, pp. 5, 15, 16 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Monitor (Con't.) | | |
| integral (Con't.) | | |
| analog | RD 74-214, p. 45 | TM-50, p. 1 |
| far field | RD 74-69, II, p. 25 | |
| glide slope | RD 73-137, p. 34 | TM-35, p. 1 |
| | RD 72-71, p. 166 | TM-44, p. 2 |
| | | TM-50, p. 6 |
| localizer | RD 73-137, p. 200 | TM-37, p. 1 |
| | RD 72-71, p. 221 | TM-30, p. 1 |
| sideband reference | RD 74-214, p. 47 | |
| slotted cable | RD 74-94, p. 1 | |
| localizer | RD 73-137, p. 213 | |
| flight test | | TM-7, p. 7 |
| near field parameters | | TM-8, p. 1 |
| precision receiver | RD 74-89, p. 15 | |
| 7-element near field | RD 72-71, p. 221 | |
| location | | TM-18, p. 5 |
| modification | | TM-47, p. 13 |
| near field | RD 70-9, p. 55 | TM-1, p. 1 |
| | RD 73-137, p. 137 | |
| | RD 74-214, pp. 10, 29 | |
| New England region full probe | RD 73-137, p. 58 | TM-44, p. 12 |
| | RD 74-214, p. 6 | |
| non-analog | RD 71-30, p. 58 | TM-11, p. 1 |
| | RD 74-214, p. 15 | |
| Ohio/Wilcox | | TM-47, p. 18 |
| 180 degree | RD 68-60, p. 205 | |
| | RD 74-214, p. 7 | |
| | RD 72-71, p. 132 | |
| overflight | RD 73-137, p. 209 | |
| | RD 74-214, p. 17 | |
| pickups | RD 65-30, p. 34 | |
| probe element | | TM-1, p. 14 |
| receiver | RD 72-71, p. 305 | |
| reference line | | TM-8, p. 3 |
| relocation | RD 66-39, p. 45 | |
| response | | TM-23, p. 1 |
| | | TM-44, p. 11 |
| exaggerated | RD 71-30, p. 24 | |
| sampling | RD 73-137, pp. 49, 58 | TM-44, pp. 1, 15 |
| | RD 70-9, p. 55 | |
| | RD 74-214, pp. 14, 23 | |
| mechanization | RD 73-137, p. 54 | TM-44, p. 7 |
| seven element | | TM-37, p. 11 |
| near-field localizer | | TM-7, p. 1 |
| | | TM-30, p. 1 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Monitor (Con't.) | | |
| sideband reference glide slope | RD 73-137, p. 57 | TM-44, p. 9 |
| | RD 72-85, p. 7 | |
| single element | RD 70-9, p. 66 | TM-1, p. 6 |
| snow | RD 71-30, p. 21 | |
| Space Modulation Quotient (SMQ) | RD 75-201, p. 22 | |
| stability | RD 73-137, p. 213 | |
| | RD 74-214, p. 16 | |
| localizer | | TM-17, p. 1 |
| station, FAA | RD 69-44, pp. 31, 33, 209 | |
| system | RD 69-44, p. 4 | |
| | RD 66-92, p. 5 | |
| perturbations | | TM-22, p. 2 |
| time constant | RD 70-9, p. 63 | |
| tolerances on position of elements | | TM-8, p. 1 |
| weather effects | RD 73-137, p. 214 | |
| wide aperture array | RD 70-9, p. 60 | TM-5, p. 1 |
| | | TM-40, p. 8 |
| width | RD 68-60, p. 211 | TM-1, pp. 2, 11 |
| | RD 70-9, pp. 70, 81 | TM-44, p. 7 |
| Monitoring | RD 69-44, p. 2 | TM-18, p. 27 |
| | RD 74-214, p. 1 | TM-15, p. 2 |
| analog | RD 70-9, p. 55 | |
| | RD 73-137, p. 49 | |
| | RD 74-214, p. 14 | |
| below line-of-sight | RD 69-44, p. 172 | |
| below path | RD 74-214, p. 6 | |
| conical geometry | RD 72-147, p. 7 | |
| discrete | RD 74-69, I, p.3 | |
| dual | RD 69-44, pp. 46, 201 | |
| ducting | RD 69-44, p. 188 | |
| environmental far field | RD 74-214, p. 7 | |
| equipment | RD 69-44, p. 18 | |
| facilities | RD 69-44, p. 17 | |
| fixed point | RD 69-44, p. 26 | |
| glide slope | RD 74-214, p. 5 | |
| implementation | | TM-13, p. 13 |
| integral | RD 74-69, II, p. 55 | TM-44, p. 1 |
| | RD 74-214, p. 30 | |
| | RD 75-201, p. 1 | |
| analog | RD 74-69, I, p.1 | TM-44, p. 15 |
| | RD 73-137, p. 58 | |
| loops | | TM-15, p. 6 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Monitoring (Con't.) | | |
| localizer | | TM-11, p. 6 |
| middle marker | RD 72-147, p. 7 | |
| near field | RD 72-71, p. 161 | |
| | RD 74-69, I, p. 2 | |
| New England full probe | | TM-44, p. 1 |
| non-representative | RD 73-137, p. 51 | TM-44, p. 5 |
| Ohio University full probe | | TM-44, p. 1 |
| parallel | RD 69-44, p. 74 | |
| program | RD 69-44, p. 3 | |
| representative | RD 70-9, p. 55 | |
| system | RD 69-44, p. 32 | |
| high tower | RD 72-71, p. 153 | |
| system and environmental | | TM-13, p. 11 |
| Monterey proposed site area | | TM-29, p. 11 |
| Multimeter circuit | | TM-51, p. 8 |
| Multipath | RD 69-44, pp. 169, 208, 213 | |
| errors | RD 69-44, pp. 5, 11, 12 | |
| interference effects | | TM-34, p. 14 |
| signals | RD 69-44, p. 206 | |
| | RD 66-92, p. 87 | |
| Mutual, admittance | RD 72-71, p. 211 | TM-26, p. 10 |
| coupling | RD 70-9, p. 30 | TM-9, p. 1 |
| | RD 71-30, p. 39 | TM-30, p. 2 |
| | RD 72-71, p. 221 | TM-36, p. 36 |
| | | TM-37, p. 4 |
| | | TM-17, p. 9 |
| localizer array | RD 74-214, p. 14 | |
| Near field | | TM-18, p. 7 |
| Null reference | RD 73-137, pp. 72, 118 | TM-46, p. 9 |
| ground plane reduction | | TM-20, p. 5 |
| Obstruction heights | RD 72-71, p. 48 | |
| | RD 75-201, p. 6 | |
| minimum | | TM-29, p. 11 |
| Offset, antenna | RD 70-9, p. 3 | TM-28, p. 9 |
| | RD 72-71, pp. 182, 189 | |
| Omnidirectional elements | | TM-26, p. 3 |
| Operational amplifiers | | TM-45, p. 19 |
| Optical, coupling | RD 74-214, p. 187 | |
| defocussing | | TM-51, p. 4 |
| energy distribution | | TM-34, p. 14 |
| energy technique | RD 73-137, p. 19 | TM-39, p. 2 |
| fixed alignment | | TM-51, p. 12 |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Optically coupled | | TM-51, p. 10 |
| Optics, geometric | RD 73-137, pp. 8, 114, 115 | TM-46, pp. 2, 3<br>TM-34, p. 4 |
| modified | RD 73-137, p. 166 | TM-42, p. 1 |
| physical | RD 73-137, pp. 5, 114 | TM-41, p. 18<br>TM-34, p. 3<br>TM-46, p. 2 |
| Scanwell | | TM-42, p. 1 |
| TSC | | TM-42, p. 1 |
| ray | RD 73-137, pp. 115, 142<br>RD 65-30, p. 6<br>RD 68-60, p. 8<br>RD 74-214, p. 11 | TM-41, pp. 1, 2<br>TM-34, p. 18<br>TM-18, p. 1 |
| Orientation | | TM-34, p. 6 |
| aircraft | RD 74-57, pp. 10, 21 | |
| non-parallel | RD 73-137, p. 166 | TM-42, p. 1 |
| parallel | | TM-48, p. 54 |
| 747 | RD 72-71, p. 93 | |
| locations | | TM-24, p. 1 |
| Oscillatory errors | RD 69-44, p. 46 | |
| Out-of-tolerance conditions | RD 69-44, p. 23<br>RD 68-60, p. 64<br>RD 70-9, p. 19 | |
| path | | TM-31A, p. 2<br>TM-13, p. 10 |
| Overflights, detector | RD 74-214, p. 64 | TM-46, p. 1<br>TM-47, p. 4 |
| sensitivity | | TM-47, p. 9<br>TM-46, p. 9 |
| directional antenna | RD 73-137, p. 209 | TM-47, p. 2 |
| effects | RD 70-9, p. 55 | |
| interference | RD 69-44, p. 156 | |
| localizer | RD 69-44, p. 209<br>RD 72-71, p. 226<br>RD 74-94, p. 16<br>RD 73-137, p. 209 | TM-47, p. 1 |
| measurements | RD 69-44, p. 144 | |
| tests, Port Columbus | RD 74-214, p. 74 | |
| Overmodulation | | TM-9, p. 11 |
| Parasitic currents | RD 73-137, p. 179 | TM-36, p. 11 |
| suppression | RD 72-71, p. 210 | TM-26, p. 6<br>TM-36, p. 2 |
| terminal | RD 71-30, p. 41 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Path, glide | | TM-49, p. 1 |
| length | | TM-41, p. 4 |
| length difference gradient | RD 69-44, p. 231 | |
| line of sight | RD 69-44, p. 17 | |
| Permittivity, calculation | RD 66-39, p. 53 | |
| complex relative | RD 65-30, p. 54 | |
| Perturbation contour maps | RD 74-87, p. 42 | |
| maximum | RD 69-44, p. 143 | |
| due to super position | RD 69-44, p. 122 | |
| Phase, advance | RD 72-71, p. 45 | |
| anomaly | | TM-28, p. 1 |
| change, center element | RD 73-137, p. 192 | |
| tests | | TM-35, p. 1 |
| detector, 30 Hz | RD 69-44, p. 198 | |
| difference | | TM-41, p. 4 |
| lag | RD 72-71, p. 196 | |
| lateral variation | RD 72-71, p. 75 | TM-19, p. 27 |
| lead | RD 73-137, p. 60 | TM-43, pp. 1, 8, 16 |
| main sideband feeder | RD 73-137, p. 64 | TM-29, p. 3 |
| | | TM-43, p. 8 |
| middle antenna | RD 73-137, p. 51 | TM-44, p. 2 |
| shift | RD 69-44, p. 212 | TM-40, p. 3 |
| | RD 70-9, p. 57 | |
| shifter | RD 74-89, p. 23 | |
| stationary | RD 72-71, p. 299 | TM-19, p. 49 |
| vertical variation | | TM-19, p. 27 |
| Phasing | | TM-14, p. 1 |
| airborne | RD68-60, p. 300 | |
| FAA flight test | | TM-43, p. 1 |
| in-flight | RD 73-137, p. 73 | |
| methods | RD 68-60, p. 209 | |
| sideband to carrier | | TM-9, p. 21 |
| systematic method | | TM-43, p. 19 |
| Phasor, carrier | | TM-18, p. 10 |
| diagrams | | TM-18, p. 8 |
| field component | RD 72-71, p. 128 | |
| sideband | | TM-18, p. 10 |
| Photo sensor | RD 73-137, p. 102 | |
| Pittsburgh airport | RD 68-60, p. 96 | TM-14, p. 1 |
| Plants, botanical properties | RD 68-60, p. 204 | |
| selection of | RD 68-60, p. 294 | |
| Polariscope | RD 69-44, p. 163 | |
| Polarization of receiving antenna | | TM-48, p. 24 |
| vertical | RD 68-60, p. 313 | |
| | RD 69-44, p. 209 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Polarized, vertical | RD 69-44, pp. 30, 158, 163, 213 | |
| | RD 68-60, p. 210 | |
| Power, diffracted | RD 73-137, p. 150 | |
| divider | | TM-37, p. 1 |
| gain | | TM-15, p. 2 |
| receiver | RD 73-137, p. 152 | |
| sideband amplitude | RD 72-147, p. 25 | |
| | RD 75-201, p. 38 | |
| Probe, current pickup loops | | TM-15, p. 11 |
| elements | | TM-50, p. 2 |
| | | TM-35, p. 2 |
| Propagation effects | RD 69-44, p. 1 | |
| | RD 66-92, p. 47 | |
| errors | RD 69-44, pp. 46, 163, 206 | |
| far field | RD 69-44, p. 37 | |
| significant | RD 69-44, p. 48 | |
| VOR | RD 66-92, p. 1 | |
| factor | RD 70-9, p. 43 | |
| meteorological effects | RD 66-92, p. 95 | |
| paths | RD 69-44, p. 4 | |
| Quadrature clearance signal | | TM-48, p. 31 |
| phasing | RD 72-147, p. 49 | |
| Quasilinearization | RD 75-201, p. 1 | |
| of a vector set | RD 72-147, p. 22 | |
| Radiated signal, arbitrary | | TM-33, p. 2 |
| Radiation, coherent | | TM-34, p. 15 |
| field | | TM-27, p. 4 |
| | | TM-35, p. 1 |
| far zone | | TM-52, p. 4 |
| | | TM-48, pp. 4, 8 |
| side frequency | RD 72-71, p. 245 | |
| horizontal | RD 65-30, p. 42 | |
| factor | | TM-48, pp. 8, 19 |
| incoherent | RD 73-137, p. 19 | TM-39, p. 2 |
| pattern | RD 72-71, pp. 218, 259 | TM-45, p. 3 |
| | RD 71-30, pp. 14, 46 | TM-41, p. 11 |
| | | TM-20, p. 3 |
| | | TM-9, p. 14 |
| | | TM-15, p. 9 |
| plane wave | | TM-39, p. 6 |
| secondary sources | RD 65-30, p. 7 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Radiation (Con't.) | | |
| vector | RD 72-71, p. 80 | TM-34, p. 3 |
| | | TM-6, p. 11 |
| components | RD 72-71, p. 70 | TM-19, pp. 19, 22 |
| rectangular area | | TM-19, p. 32 |
| vertical plane | RD 71-30, p. 17 | |
| Radio ray curvature | RD 69-44, p. 7 | |
| Radio telemetering theodolite (RTT) | RD 68-60, p. 210 | TM-45, p. 2 |
| | RD 72-71, p. 28 | TM-51, p. 1 |
| | RD 74-214, p. 178 | |
| reference | RD 74-214, p. 22 | |
| Radius of curvature | | TM-41, p. 14 |
| Range, dynamic | | TM-51, p. 8 |
| effects | | TM-51, p. 2 |
| Receiver, bandpass | | TM-33, p. 9 |
| characteristics | RD 69-44, p. 122 | TM-33, p. 23 |
| | RD 72-71, p. 251 | |
| improved design | RD 69-44, p. 209 | |
| drift | RD 69-44, p. 181 | |
| effects | RD 69-44, p. 146 | |
| glide path | | TM-23, p. 6 |
| response | RD 69-44, p. 184 | TM-33, p. 7 |
| Receiving equipment | RD 69-44, p. 206 | |
| recording system | RD 69-44, p. 105 | |
| Records, compressed | RD 69-44, p. 33 | |
| Reflected field | RD 68-60, pp. 11, 100, 172 | |
| | RD 72-147, p. 66 | |
| expression | RD 68-60, p. 98 | |
| fuselage | RD 73-137, p. 156 | TM-41, p. 15 |
| near field | RD 66-39, p. 7 | |
| radiation, incremental area | RD 68-60, p. 239 | |
| sideband field strength | | TM-41, p. 16 |
| signal | RD 69-44, p. 30 | TM-41, p. 10 |
| | RD 68-60, pp. 22, 127 | TM-46, p. 2 |
| | | TM-18, p. 10 |
| localizer | RD 74-214, p. 13 | |
| total | RD 65-30, p. 10 | |
| | RD 68-60, p. 8 | |
| wave | RD 73-137, pp. 148, 240 | TM-34, p. 24 |
| | | TM-41, p. 6 |
| Reflecting aircraft | RD 69-44, p. 234 | |
| surfaces parallel to runway | | TM-41, p. 21 |
| Reflecting screens | RD 74-214, p. 14 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Reflection, aircraft | RD 71-30, p. 25 | |
| anomalous | | TM-27, p. 5 |
| coefficient | RD 72-71, pp. 133, 193, 195 | TM-32, pp. 4, 5 |
| | | TM-22, p. 7 |
| | RD 66-92, p. 89 | TM-18, p. 10 |
| | RD 65-30, pp. 17, 32, 46 | |
| | RD 69-44, p. 9 | |
| air-snow | RD 66-39, p. 45 | |
| modified | RD 65-30, p. 51 | |
| from conductors | RD 69-44, p. 14 | |
| allowable derogation | | TM-34, p. 12 |
| from a flat plane | RD 65-30, pp. 11, 43 | |
| frontal | RD 69-44, p. 8 | |
| model | RD 74-89, p. 4 | |
| pattern, free space | RD 73-137, p. 17 | |
| ray optic point | RD 68-60, p. 127 | |
| Reflections, aircraft | RD 72-71, p. 50 | TM-39, p. 3 |
| effect of | | TM-19, p. 1 |
| glide path | | TM-19, p. 1 |
| hangar walls | RD 70-9, p. 22 | |
| specular | RD 73-137, p. 142 | TM-41, p. 1 |
| | RD 65-30, p. 4 | TM-39, p. 3 |
| | | TM-42, p. 5 |
| spurious | RD 72-71, p. 302 | TM-32, p. 6 |
| | | TM-15, p. 2 |
| vertical walls | RD 71-30, p. 35 | |
| Refraction, index of | RD 69-44, p. 7 | |
| discontinuity | RD 69-44, p. 14 | |
| Repeatability of flight tracks | RD 68-60, p. 187 | |
| Reradiated energy | RD 68-60, p. 102 | |
| Reradiation | | TM-2, p. 3 |
| from wire | RD 72-71, p. 195 | |
| fuselage surface currents | | TM-6, p. 9 |
| pattern | | TM-34, p. 16 |
| Resonators, H-shape | RD 69-44, p. 211 | |
| Responses, 51 R-3 | | TM-33, p. 9 |
| Resultant signal | RD 66-92, p. 87 | |
| Roughness, course | RD 68-60, p. 117 | |
| glide path | RD 68-60, p. 197 | TM-24, p. 1 |
| Safety factor | | TM-34, p. 14 |
| Scalloping | RD 69-44, p. 31 | TM-26, p. 15 |
| | RD 72-71, p. 218 | TM-34, p. 15 |
| course | RD 69-44, p. 211 | TM-48, p. 34 |
| | RD 74-57, p. 56 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Scalloping (Con't.) | | |
| frequency | RD 70-9, p. 63 | TM-1, p. 3 |
| | RD 69-44, p. 16 | TM-41, p. 17 |
| | RD 73-137, p. 170 | TM-42, p. 6 |
| | RD 74-89, p. 6 | |
| Scattering, electromagnetic | RD 70-9, p. 34 | TM-6, p. 1 |
| field | RD 70-9, p. 42 | |
| | RD 72-71, p. 57 | |
| total | RD 72-71, p. 81 | |
| location of object | | TM-48, p. 29 |
| resultant field | | TM-48, pp. 10, 29 |
| Schelkunoff radiation vector | RD 72-71, pp. 76, 83 | TM-19, p. 28 |
| Scintillation effects | RD 69-44, p. 38 | |
| Screen, height | | TM-36, pp. 1, 3 |
| large mesh | | TM-36, p. 14 |
| optimal positions | | TM-36, p. 7 |
| size | | TM-36, p. 5 |
| Sensor currents | | TM-51, p. 5 |
| parameters | | TM-45, p. 7 |
| photo | | TM-45, p. 2 |
| Servo amplifier | RD 73-137, p. 110 | TM-45, p. 15 |
| motor | | TM-45, p. 19 |
| 747, Boeing | | TM-19, pp. 37, 46 |
| Shadow region | | TM-48, p. 6 |
| obstacles | | TM-48, p. 26 |
| term | | TM-52, p. 5 |
| | | TM-48, p. 26 |
| Sideband | RD 69-44, p. 14 | |
| dephasing | RD 72-71, p. 189 | TM-28, p. 4 |
| direct voltage | | TM-19, p. 34 |
| feeder phase lead | RD 73-137, p. 64 | TM-29, p. 3 |
| | | TM-43, p. 8 |
| field | | TM-2, p. 3 |
| patterns | RD 72-71, p. 202 | TM-20, p. 3 |
| | RD 71-30, p. 81 | TM-26, p. 1 |
| reference system | RD 68-60, p. 208 | |
| data | | TM-29, p. 10 |
| modified | | TM-4, p. 6 |
| signal | | TM-21, p. 1 |
| | | TM-26, p. 3 |
| Signal level | RD 69-44, pp. 46, 48, 103, 184, 212 | |
| change | RD 69-44, p. 157 | |
| far field | | TM-35, p. 4 |
| to noise ratio | | TM-45, p. 6 |
| strength | RD 69-44, p. 26 | |
| | RD 66-92, pp. 26, 33, 73, 94, 147 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Site analysis, computer | RD 68-60, p. 211 | |
| effects | RD 71-30, p. 41 | |
| Site types | RD 74-214, p. 90 | |
| Siting criteria | RD 72-71, p. 8 | |
| Siting problem | RD 74-214, p. 3 | |
| Sliding scale | RD 72-71, p. 5 | TM-31A, p. 4 |
| Slope, uniform | | TM-14, p. 12 |
| Slotted cable array | RD 74-94, p. 1 | |
| Snow accumulations | RD 66-39, p. 15 | |
| | RD 68-60, p. 16 | |
| cover | RD 75-201, p. 24 | |
| computer program | RD 65-30, p. 64 | |
| effect of | RD 66-39, p. 17 | TM-18, p. 19 |
| | RD 74-69, II, p. 12 | |
| in reflection zone | RD 74-214, p. 169 | |
| data collection | RD 73-137, p. 137 | TM-13, p. 8 |
| | | TM-23, p. 2 |
| density | RD 65-30, p. 60 | |
| depth | RD 74-69, I, p. 2 | TM-18, p. 6 |
| | RD 73-137, p. 140 | |
| | RD 72-85, p. 1 | |
| | RD 72-71, p. 157 | |
| | RD 68-60, p. 84 | |
| contour maps | RD 68-60, p. 74 | |
| measurements | | TM-23, p. 6 |
| versus DDM | RD 72-85, p. 13 | |
| dielectric | RD 68-60, pp. 16, 25 65, 205 | TM-18, p. 7 |
| | RD 72-85, p. 13 | |
| | RD 66-39, p. 15 | |
| disposition of | RD 65-30, p. 34 | |
| effects | RD 72-71, p. 153 | TM-36, p. 7 |
| | RD 68-60, p. 205 | TM-13, pp. 1-4 |
| computer program | RD 68-60, p. 245 | |
| | RD 66-39, p. 47 | |
| on glide path | RD 74-214, pp. 30, 91 | |
| angle | RD 68-60, p. 60 | |
| | RD 66-39, pp. 3, 55 | |
| no | | TM-23, Appendix A |
| ground cover | RD 72-71, p. 128 | |
| intermittent | | TM-23, Appendix A |
| layer | RD 71-30, p. 21 | |
| | RD 68-60, p. 57 | |
| continuous deep | | TM-23, Appendix A |
| effects on modified sideband reference | RD 68-60, p. 44 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Snow accumulation (Con't.) | | |
| layer (Con't.) | | |
| multiple | RD 68-60, p. 207 | |
| | RD 66-39, p. 4 | |
| thickness | RD 68-60, p. 22 | |
| monitor system | RD 71-30, p. 21 | |
| occasional | | TM-23, Appendix A |
| parameters | | TM-13, p. 11 |
| reflections | RD 65-30, p. 56 | |
| removal | RD 68-60, p. 206 | |
| sites | | TM-23, p. 3 |
| surface | RD 72-85, pp. 1, 7, 15 | |
| totalling reflecting | RD 72-71, p. 130 | TM-18, p. 4 |
| wet | RD 65-30, p. 29 | |
| Snowfall, new | RD 72-85, p. 7 | |
| Soil conditions | RD 70-9, p. 18 | |
| | RD 68-60, pp. 86, 206 | |
| | RD 74-214, p. 3 | |
| sampler | RD 66-39, pp. 40, 81 | |
| Space Modulation Quotient (SMQ) | RD 75-201, p. 20 | |
| Spacial frequency | RD 71-30, p. 62 | TM-32, p. 3 |
| | RD 72-71, p. 195 | |
| Spacing, aircraft | | TM-48, p. 36 |
| Spectra, line | RD 74-89, p. 20 | |
| Spectral response | | TM-45, p. 8 |
| Specular point | RD 73-137, pp. 126, 128, 153, 233 | TM-34, pp. 4, 18, 21, 23<br>TM-46, pp. 3, 5, 16, 18 |
| method | RD 72-71, p. 94 | |
| reflection | RD 73-137, p. 115 | TM-41, p. 14 |
| reflected signal | | TM-20, p. 2 |
| reflections | RD 65-30, p. 4 | TM-39, p. 3 |
| | RD 73-137, p. 142 | TM-41, p. 1 |
| | | TM-42, p. 5 |
| Spreading correction factor | | TM-39, p. 1 |
| Spurious reflections | | TM-32, p. 6 |
| | | TM-15, p. 2 |
| sideband signals | RD 72-71, p. 302 | |
| Stability of operation | RD 66-92, p. 93 | |
| Standing wave reflection (SWR) | RD 71-30, pp. 14, 50 | TM-15, p. 3 |
| colinear dipole array | | TM-15, p. 7 |
| Static CDI | | TM-42, p. 7 |
| Summer, algebraic | RD 68-60, p. 229 | |
| Superposition errors | RD 69-44, pp. 11, 14 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Tailfin | RD 74-57, p. 10 | TM-10, p. 14 |
| | RD 74-89, p. 5 | TM-41, pp. 4, 10 |
| incident H-field | | TM-19, p. 26 |
| reflections | RD 73-137, p. 243 | TM-34, p. 27 |
| vertical | RD 71-30, p. 75 | TM-19, p. 26 |
| | RD 72-71, p. 73 | |
| TE coefficients | | TM-10, p. 3 |
| cylindrical waves | RD 70-9, p. 45 | TM-6, p. 8 |
| | RD 72-71, p. 59 | TM-19, p. 11 |
| wave coefficients | RD 70-9, p. 46 | TM-19, p. 12 |
| | RD 72-71, p. 60 | |
| Telemetry link | RD 69-44, p. 23 | TM-51, p. 18 |
| Telescope | | TM-45, p. 6 |
| Temperature effects on angle | RD 68-60, p. 75 | |
| operating | RD 69-44, p. 186 | |
| sensitivity | RD 74-89, p. 39 | |
| Tensors | | TM-34, pp. 24-25 |
| Terrain, Columbus, Ohio | RD 68-60, p. 190 | |
| discontinuities | RD 72-147, p. 62 | |
| down sloping | | TM-27, p. 3 |
| effects of irregular | RD 74-214, p. 3 | |
| elevation | RD 68-60, p. 131 | |
| flat | RD 66-39, p. 25 | |
| | RD 68-60, p. 97 | |
| grading | RD 68-60, p. 173 | |
| | RD 71-30, p. 3 | |
| optimum | RD 68-60, p. 134 | |
| irregular | RD 72-71, p. 301 | TM-7, p. 8 |
| non-standard grading | RD 72-71, p. 27 | |
| non-uniform | RD 68-60, p. 108 | |
| | RD 70-9, p. 101 | |
| perpendicular | RD 68-60, p. 105 | |
| reflecting | RD 70-9, p. 94 | |
| slopes | | TM-12, p. 1 |
| uniform | RD 71-30, p. 3 | TM-12, pp. 4-5 |
| Theodolite | | TM-23, p. 6 |
| location | RD 74-69, II, p. 48 | |
| placement | RD 68-60, p. 290 | TM-31A, pp. 5, 9, 10 |
| | RD 72-71, pp. 5, 8, 11 | |
| | RD 73-137, p. 84 | |
| | RD 74-214, p. 13 | |
| radio | RD 66-39, p. 44 | TM-7, p. 8 |
| | RD 68-60, p. 114 | |
| references | RD 68-60, p. 64 | |
| | RD 69-4, p. 2 | |
| | RD 72-71, p. 3 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| Threshold | | TM-45, p. 8 |
| crossing height (TCH) | RD 68-60, p. 190 | TM-14, pp. 1, 5, 9 |
| | RD 71-30, pp. 29, 30, 32 | |
| | RD 72-71, pp. 28, 30, 49 | |
| | RD 73-137, p. 86 | |
| | RD 74-214, pp. 20, 21 | |
| Tilt switch alarm | RD 74-69, I, p. 2 | |
| Time constant | | TM-42, p. 7 |
| sharing | RD 69-44, p. 23 | |
| TM coefficients | | TM-10, p. 1 |
| cylindrical waves | | TM-6, p. 13 |
| wave expansion | RD 70-9, p. 42 | TM-19, p. 9 |
| | RD 72-71, pp. 57, 58 | |
| Tolerance criterion | | TM-34, p. 12 |
| Tone balance | | TM-27, p. 2 |
| Topographic information | | TM-31A, p. 10 |
| Tracking, automatic system | | TM-45, p. 1 |
| azimuth | RD 72-71, pp. 20, 27 | |
| dynamic | RD 74-214, p. 31 | |
| lights | | TM-45, p. 21 |
| static | RD 74-214, p. 33 | |
| Transfer function | RD 69-44, p. 212 | TM-45, p. 15 |
| Transmission coefficient | RD 65-30, p. 49 | |
| line analogy | | TM-18, p. 1 |
| Transmitting equipment | | TM-49, p. 1 |
| Travis AFB site | RD 72-71, p. 14 | TM-46, p. 18 |
| Tropospheric duct | RD 69-44, pp. 12, 103 | |
| effects | RD 69-44, p. 206 | |
| Truncated ground theory | RD 73-137, p. 73 | |
| TSC report | | TM-41, pp. 18-19 |
| Under planting technique | RD 68-60, p. 294 | |
| Vegetation effects | RD 68-60, p. 232 | |
| Vertical polarized signal | RD 69-44, pp. 30, 158, 163, 213 | |
| | RD 68-60, p. 210 | |
| Voltage regulation | RD 69-44, p. 38 | |
| VOR, accuracy | RD 66-92, p. 1 | |
| available | RD 69-44, pp. 1, 3 | |
| maximum | RD 66-92, p. 93 | |
| course data | RD 69-44, p. 17 | |
| error | RD 69-44, p. 1 | |
| doppler | RD 69-44, p. 211 | |
| mathematical model | RD 69-44, p. 119 | |
| Parkersburg | RD 66-44, p. 143 | |
| path deviations | RD 66-92, p. 38 | |
| Phoenix, Arizona | RD 69-44, p. 120 | |

| | FAA RD NUMBER | TECHNICAL MEMORANDUM NUMBER |
|---|---|---|
| VOR (Con't.) | | |
| propagation error | RD 69-44, pp. 46, 163, 206 | |
| receiver design | | |
| characteristics | RD 69-44, p. 212 | |
| error | RD 66-92, p. 3 | |
| reflected signals | RD 69-44, p. 156 | |
| tolerances | RD 69-44, p. 1 | |
| V-ring, array | | TM-33, p. 4<br>TM-36, p. 1 |
| signal | | TM-33, p. 2 |
| Watts slotted cable end-fire array | RD 74-214, p. 59 | |
| Wave expansion coefficients | | TM-19, p. 10 |
| Wavenumber, local | RD 72-71, p. 57 | TM-19, p. 9 |
| Weather effects | RD 69-44, p. 53 | |
| Width, glide path | RD 68-60, p. 144 | TM-33, p. 23 |
| tolerance | | TM-33, pp. 24, 25 |
| Wires, reradiation from | | |
| spacing and diameter | | TM-32, p. 3<br>TM-32, pp. 5, 6 |